



ICPE2600 Series

Wall Mounting or Pole Mounting

Industrial Outdoor 5G Wireless Router

- Support 1 Gigabit PoE WAN, 1 Gigabit LAN, 2 2.4G antenna interfaces, 2 5.8G antenna interfaces and 4 5G Sub- 6G antenna interfaces, which can meet the high bandwidth requirement of industry application.
- Support 5G NR cellular wireless network, compatible with 3G/4G LTE all networks
- Support 2.4GHz and 5.8GHz dual bands
- Support 12~48VDC power supply input , and WAN port supports 48VDC PoE power supply input
- Support -40~75°C wide operating temperature range



Introduction

ICPE2600 series is industrial 5G wireless router. Its PoE power supply conforms to IEEE802.3af/at protocol standard. This series has two products, provides Gigabit PoE WAN, Gigabit LAN, 2.4G antenna interfaces, 5.8G antenna interfaces and 5G Sub-6G antenna interfaces. They also adopt wall mounting or pole mounting, which can meet the requirements of different application scenes.

Network management supports multiple software functions, like 3G/4G/5G Cellular WAN, Ethernet WAN, ICMP Link Test, Link Backup, Dynamic Domain Name, Routing Table Setting, WLAN Setting, Port Forwarding, Port Redirection, DMZ Settings, UPnP Setting, VRRP, RIP, OSPF, Static DHCP, QoS etc. It also supports firewall functions, such as IP Filtering, MAC Filtering, URL Filtering and Keyword Filtering and VPN tunneling functions including GRE, IPSec, PPTP, L2TP. It can provide users with good experience with friendly design of network management system interface, simple and convenient operation.

RESET button can realize device reboot and one-key factory default restoration. All components are industrial grade, and the protection grade is IP68, which can adapt to the harsh outdoor environment. It can be widely used in rail transit, security, smart city, integrated pipe gallery, production automation, smart lamp pole and other industries.


Features and Benefits

- ⦿ Support high-speed wireless connection, 2.4GHz transmission speed could reach 300Mbps, 5.8GHz could reach 867Mbps, 5G Sub-6G could reach 2Gbps
- ⦿ Supports dual-band 2×2MIMO and 4 dual-RF omnidirectional antennas; Support 5G Sub-6G 4×4MIMO and 4 omnidirectional antennas
- ⦿ Support dual SIM card redundancy backup and Cellular network. It's embedded with 5G wireless communication modules
- ⦿ Support PPPoE dialing, IP acquisition by DHCP, backup switch between static IP and 3G/4G/5G cellular networks to fit different scenes
- ⦿ Support network firewall, which can implement filtering and forwarding of IP, MAC, URL, keyword, etc.
- ⦿ Support DHCP server, which can be used for distributing IP address with different strategies
- ⦿ Support DDNS function, user can access server through domain names
- ⦿ Support VPN encryption protocols like GRE, PPTP, L2TP and IPSEC, which can ensure the privacy and integrity of data and prevent replay attack
- ⦿ Support port forwarding, port redirection functions and so on, which can realize address translation
- ⦿ VRRP, RIP, OSPF could implement dynamic router configuration
- ⦿ QoS supports real-time traffic classification and priority setting

- Support system log, ping test and route tracking, user can conduct network diagnosis and troubleshooting.

Dimension

Unit: mm



Specification

Standard & Protocol	<p>IEEE 802.3 for 10Base-T IEEE802.3u for 100Base-TX IEEE 802.3ab for 1000Base-T 3GPP Rel-15 for 5G NR 3GPP Rel-14 for 4G LTX 3GPP Rel-18 for 3G WCDMA IEEE802.11b/g/n/a/ac for WLAN IEEE802.11i for wireless security IEEE802.11r for fast roaming IEEE802.3af/at for PoE/PoE+</p>
Cellular Network	<p>3G/4G/5G cellular network, network type 5G NR/LTE FDD/ LTE TDD/ WCDMA/ TD-SCDMA/ HSPA/ CDMA/ EVDO</p>
Network Settings	<p>WAN Network, Wireless WiFi, PPPoE Dialing, Link Backup, Dynamic Domain Name, Routing Table, Wireless Client Filtering, Port Forwarding , Port Redirection, DMZ Settings, UPnP Settings, Static DHCP, QoS, VRRP, RIP, OSPF</p>
Firewall	<p>IP Filtering, MAC Filtering, URL Filtering and Keyword Filtering</p>
VPN Tunnel	<p>GRE, PPTP Client/Server, L2TP Client/Server, IPSec</p>
System Management	<p>Time Settings, Access Settings, Timed Restart, Backup Recovery, Log Management, Firmware Upgrade</p>

Troubleshooting	System Log, Ping Test and Route Tracking
WiFi Radio Frequency	802.11B/g/n: 2.412GHz~2.4835GHz 802.11Ac/n/a: 5.18GHz~5.825GHz RF power output: 20dBm Modulation methods: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
WiFi Receiving Sensitivity	802.11n_HT40: -82dBm@MCS0, -64dBm@MCS7 802.11n_HT20: -85dBm@MCS0, -67dBm@MCS7 802.11g/a: -91dBm@6Mbps, -72dBm@54Mbps 802.11b: -93dBm@1Mbps, -87dBm@11Mbps 802.11ac: -84dBm@MCS0, -59dBm@MCS9
WiFi Transmitting Power	802.11n_HT40: 20dBm@MCS0, 20dBm@MCS7 802.11n_HT20: 20dBm@MCS0, 20dBm@MCS7 802.11g/a: 20dBm@6Mbps, 20dBm@54Mbps 802.11b: 20dBm@1Mbps, 20dBm@11Mbps 802.11ac: 20dBm@MCS0, 20dBm@MCS9
5G NR Operating Frequency Band	ICPE2600-BW-8A25-2GT-PDP12_48: <ul style="list-style-type: none"> 5G NR: n78/n79/n41 4G LTE: B1/B3/B5/B8/B34/B38/B39/B40/B41 3G WCDMA: B1/B8 ICPE2600A-BW-8A25-2GT-PDP12_48: <ul style="list-style-type: none"> 5G NR: n1/n2/n3/n5/n7/n8/n12/n20/n28/n38/n40/n41/n48/n66/n71/n77/n78/n79 4G LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B9/B12/B13/B14/B17/B18/B19/B20/B25/B26/B28/B29/B30/B32/B66/B71 4G LTE-TDD: B34/B38/39/B40/B41/B42/B48 3G WCDMA: B1/B2/B3/B4/B5/B6/B8/B19
5G NR Bandwidth (downward, upward)	ICPE2600-BW-8A25-2GT-PDP12_48: <ul style="list-style-type: none"> 5G NR: DL 2Gbps; UL 230Mbps (Theoretical rate) LTE-TDD: DL 1Gbps; UL 30Mbps LTE-FDD: DL 600Mbps; UL 75Mbps 3G (DC-HSPA+): DL 42Mbps; UL 5.76Mbps 3G (HSPA+): DL 21Mbps; UL 5.76Mbps ICPE2600A-BW-8A25-2GT-PDP12_48: <ul style="list-style-type: none"> 5G SA: DL 2.1Gbps; UL 900Mbps 5G NSA: DL 2.5Gbps; UL 650Mbps LTE: DL 1Gbps; UL 200Mbps WCDMA: DL 42Mbps; UL 5.76Mbps

<p>Interface</p>	<p>WAN port: 1 10/100/1000Base-T(X) RJ45port, support POE 48VDC input power supply LAN port: 1 10/100/1000Base-T(X) RJ45 port Antenna: 2 2.4G N-K type (Female) interfaces, 2 5.8G N-K type (Female) interfaces, 4 5G Sub-6G N-K type (Female) interfaces SIM cart slot: 1 Micro SIM card slot and 1 Nano SIM card slot, redundant backup</p>									
<p>Power supply</p>	<p>WAN port: supports PoE 48VDC power receiving, which conforms to IEEE802.3af/at standard Power supply terminal: 12~48VDC, support non-polarity, using 3-pin 5.08mm pitch terminal with waterproof plug</p>									
<p>Indicator</p>	<p>Running status indicator, WLAN indicator, 5G indicator, WLAN indicator, LAN indicator, 5G signal strength indicator</p>									
<p>Power consumption</p>	<table border="1"> <thead> <tr> <th data-bbox="699 882 1043 990">Available Models</th> <th data-bbox="1043 882 1235 990">No-load (normal temperature)</th> <th data-bbox="1235 882 1439 990">Full-load (high temperature)</th> </tr> </thead> <tbody> <tr> <td data-bbox="699 990 1043 1070">ICPE2600-BW-8A25-2GT-PDP12_48</td> <td data-bbox="1043 990 1235 1070">5.8W</td> <td data-bbox="1235 990 1439 1070">18.3W</td> </tr> <tr> <td data-bbox="699 1070 1043 1151">ICPE2600A-BW-8A25-2GT-PDP12_48</td> <td data-bbox="1043 1070 1235 1151">5.5W</td> <td data-bbox="1235 1070 1439 1151">15.9W</td> </tr> </tbody> </table>	Available Models	No-load (normal temperature)	Full-load (high temperature)	ICPE2600-BW-8A25-2GT-PDP12_48	5.8W	18.3W	ICPE2600A-BW-8A25-2GT-PDP12_48	5.5W	15.9W
Available Models	No-load (normal temperature)	Full-load (high temperature)								
ICPE2600-BW-8A25-2GT-PDP12_48	5.8W	18.3W								
ICPE2600A-BW-8A25-2GT-PDP12_48	5.5W	15.9W								
<p>Working Environment</p>	<p>Operating temperature: -40~75℃ Storage temperature:-40~85℃ Relative humidity: 5%~95%(no condensation)</p>									
<p>Physical Characteristic</p>	<p>Housing: IP68 protection, metal Installation: Wall mounting or pole mounting Dimension (L × W × H): 275mm×76mm×245mm Weight: 3kg</p>									
<p>Industrial Standard</p>	<p>IEC 61000-4-2 (ESD, electrostatic discharge), Level 4</p> <ul style="list-style-type: none"> Air discharge: ±15kV Contact discharge: ±8kV <p>IEC 61000-4-4 (EFT, electrical fast transient), Level 4</p> <ul style="list-style-type: none"> Power supply: ±4kV Ethernet interface: ±2kV <p>IEC 61000-4-5 (Surge), Level 4</p> <ul style="list-style-type: none"> Power supply: common mode±4kV, differential mode±2kV Ethernet interface: ±4kV 									

	Shock: IEC 60068-2-27 Free fall: IEC 60068-2-32 Vibration: IEC 60068-2-6
MTBF	>250000 hours
Authentication	CE, FCC, RoHS
Warranty	5 years



Ordering Information

Available Models	Gigabit PoE WAN	Gigabit LAN	Antenna interface			Power supply
			2.4G	5.8G	5G Sub-6G	
ICPE2600-BW-8A25-2GT-PDP12_48	1	1	2	2	4	12~48VDC or PoE 48VDC
ICPE2600A-BW-8A25-2GT-PDP12_48						

Optional Accessories

Product Type	Product Number	Remark
2.4GHz(5dBi) omnidirectional fiberglass antenna, N-J type×1	3005040017	Optional
5.8GHz(5dBi) omnidirectional fiberglass antenna, N-J type×1	3005040019	Optional
2.4GHz(8dBi) omnidirectional fiberglass antenna, N-J type×1	3005040012	Optional
5.8GHz(8dBi) omnidirectional fiberglass antenna, N-J type×1	3005040013	Optional
2.4GHz(14dBi) directional panel antenna, N-K type×1	3005040010	Optional
5.8GHz(14dBi) directional panel antenna, N-K type×1	3005040011	Optional
5G Sub-6G (3dBi) omnidirectional fiberglass antenna, N-J type×1	3005040064	Optional
5G Sub-6G (5dBi) omnidirectional fiberglass antenna, N-J type×1	3005040082	Optional
5M outdoor waterproof WLAN RF cable, NJ-NK	3005040008	Optional
5M outdoor waterproof WLAN RF cable, NJ-NJ	3005040014	Optional



Address: 3/B, Zone 1, Baiwangxin High Technology Industrial Park, Song Bai Road, Nanshan District, Shenzhen, 518108, China

TEL.: +86-755-26702668 ext 835 FAX: +86-755-26703485

E-mail: ics@3onedata.com

Website: www.3onedata.com

⬇ Please scan our QR code for more details

*Product pictures and technical data in this datasheet are only for reference. Updates are subject to change without prior notice. The final interpretation right is reserved by 3onedata.